Whiting Hinged Truss II Dry Freight Roll-Up Door



The only door which may outlive your vehicle!

Double wall aluminum extruded panels form a truss to make this dry freight door the most durable and strongest door Whiting has available. This superior door readily accepts automotive quality paint and decals and will not swell, chip or warp.

PVC joint cover guards against oxidation streaking. Sloped design with weather seals keeps moisture out.

Equipped with 2" roller and 2" track to withstand rough service, this door is the last one you will buy for your fleet.

Also available with optional steel rollers and stainless steel hardware.



Heavy duty bottom roller bracket designed for easy roller replacement.

Product Features

Durable double wall extruded aluminum panels
Double sealed contoured panel joints
Heavy duty 7181 bottom roller brackets
No thru-rivets allows for easy decaling
Two spring independent suspension balancer
2" track and roller system

End hinges with easy roller change feature
Heavy duty bottom panel with replaceable seal
All door hardware E-Coated to prevent rust and
corrosion

Self adjusting cam lock and other lock options available



Extruded reinforcement section is added to the bottom panel and anywhere additional strength is required.





End hinge and roller carrier. Removable cap allows roller change without removing hinge.

Questions? Call Whiting for more information



Corporate Office: 113 Cedar Street Akron, New York 14001 Phone: (716) 542-5427 Fax: (716) 542-5947

e-mail: info@whitingdoor.com

California Office:

301 S. Milliken Avenue Ontario, California 91761 Phone: (909) 877-0120 Fax: (909) 877-9180

web: whitingdoor.com



