



DOOR PANEL SECTIONS

NOTE: 6-1/2" (165.1MM) RADIUS TRACK WILL ACCOMMODATE NOTHING WIDER THAN 5" PANELS (UNLESS BOTH ENDS OF 6" PANEL ARE NOTCHED BY WHITING, SEE B-2118 FOR DETAILS)

TO DETERMINE PANEL SIZE AND QUANTITIES:

- SUBTRACT 4" [101.6MM] FROM SILL TO HEADER. (THE 4" [101.6MM] IS DERIVED FROM THE 3" [76.2MM] BOTTOM PANEL AND HALF OF THE 2" [50.8MM] TOP PANEL).
- DIVIDE THIS MEASUREMENT BY ANY COMBINATION OF 5" [127.0MM] AND 3-3/8" [85.7MM] INTERMEDIATE PANELS. IT IS MORE COST EFFECTIVE TO USE MORE OF THE 5" [127.0MM] PANELS. DO NOT USE 6" [152.4MM] ON 6-1/2" [165.1MM] RADIUS TRACK, UNLESS ENDS ARE NOTCHED.
- COMPARE PANES SIZES AND QUANTITIES TO THE "SILL TO HEADER". TOP SEAL LOCATION MUST *NOT* FALL BELOW HEADER.

NOTE:
SEE PARTS BOOK FOR MORE INFORMATION; ALSO SEE D-9911 FOR OPTIONAL 2-POINT LOCK REFER TO: D-9920, 9920-1 (INSTALLATION)

| | | | | |
|------------------------------|---|-----------------------|------|---------------|
| 5/5/11 | G | UPDATE PRINT | M/S | AF |
| 4/20/92 | F | REDRAWN ON C/D | M/S | JMY |
| DATE | SYM | DESCRIPTION OF CHANGE | AUTH | DR |
| REVISIONS | | | | |
| TOLERANCES (EXCEPT AS NOTED) | WHITING DOOR MANUFACTURING CORP. GENERAL OFFICE: 113 CEDAR ST. AKRON, NY. 14001 "DEVELOPER OF THE FIRST PRACTICAL ROLL-UP DOOR IN 1953" | | | SEA-LOK DOORS |
| DECIMAL ±.010 | | | | SCALE 1/2 |
| FRACTION ±1/16 | TITLE GENERAL INSTALLATIONS BEVERAGE BODY EXTRUDED ALUMINUM PANELS | | | |
| ANGULAR ±1/2 | DATE 3/22/73 | DWG. NO. D-2085 | REV. | G |